



Dräger PSS® 5000 Compressed Air Breathing Apparatus

The Dräger PSS® 5000 SCBA is a high-performance breathing apparatus for the professional firefighter. Combining advanced ergonomics with a wide range of configurable options, the Dräger PSS® 5000 provides the user with the comfort and versatility to meet the demands of first responders whenever breathing protection is required.



Benefits

Dräger PSS® 5000

- Ergonomic carrying system
- Advanced harness choice
- Service friendly & easy to maintain
- Integrated and Versatile hose routing
- Wide variety of system configurations and accessories
- Electronic Monitoring with the Dräger Bodyguard® 1500 and Bodyguard® 7000 systems

Utilizing the established Dräger PSS 7000 pneumatics and cylinder strap design, the Dräger PSS 5000 combines established technology, state-of-the-art materials and innovative thinking to create an SCBA for virtually any application.

Ergonomic carrying system

The Dräger PSS 5000 has been designed to be not only comfortable but also extremely stable during use in harsh firefighting environments. Incorporating a rigid harness connection to a fixed-height back plate, advanced harness materials and a pivoting waist belt, the Dräger PSS 5000 remains in position regardless of the task in hand.

Advanced harness choice

To allow the breathing apparatus to be tailored to the required application, the Dräger PSS 5000 utilizes state-of-the-art harness materials offered in a choice of 2 harness options:

The Dräger Standard (DS)

Harness is a cost effective option for everyday use, offering a high level of comfort and durability. Easy to don and doff materials and simple pull forward and pull down adjustment mechanisms make the DS harness a versatile option for a wide variety of applications.

The Dräger Professional (DP)

Utilizes materials to withstand the high wear and tear that firefighters face daily, whilst providing an enhanced level of durability over the DS harness. Incorporating hardwearing stainless steel buckles and long-life Aramid blend webbing, the DP is ideally suited to extended wear and frequent use.

Service friendly & easy to maintain

To keep downtime and costs to a minimum during service and maintenance, the Dräger PSS 5000 incorporates a number of unique design features

- Dräger's innovative Harness "slide and lock" mechanism facilitates fast and simple harness and waist pad connection/removal from the back plate, without the use of tools
- The first stage reducer snap fit connection allows the pneumatics to be fitted or removed quickly and easily from the set

Benefits

- "Push in and out" hose clips allow swift removal of hoses from the harness pads for cleaning, without the need to remove the clip itself
- Closed, single piece harness and waist pad design to prevent excessive water absorbtion, reducing cleaning and drying time

Integrated and versatile hose routing

Tominimize the risk of snagging and to guard against physical damage, both the gauge and air supply hoses are integrated within channels in the Dräger PSS 5000 back plate. The LDV, Gauge and Rescue hoses can now be routed over the left and/or right shoulders (2 hoses per side), allowing the Dräger PSS 5000 to be configured to any standard. Conventional waistmounted hoses can also be fittedmaking the Dräger PSS 5000 one of the most versatile SCBA's available.

Wide variety of system configurations and accessories

Dräger has revolutionized the use of breathing apparatus by creating a range of components that can be selected in combination to meet the specific needs of the firefighter regardless of the task.

In addition to the inherent features of the Dräger PSS 5000 DS and DP, it is also possible to add

- Dräger Bodyguard 7000 electronic monitoring
- Dräger Bodyguard 1500 integrated PASS when used with Tx gauge
- Twin cylinder configuration
- Quick-Connect (QC) cylinder connection
- ChargAir quick filling
- Secondary supply connections for rescue, decontamination and/or airline use
- Dräger PSS® Merlin® Modem
- Dräger PSS® Rescue Hood
- Dräger PSS® SafetyBelt
- And many more ... (for a full list and information please refer to the Dräger CABE Family Catalogue)

Electronic monitoring with the Dräger Bodyguard 7000

The Dräger PSS 5000 has been designed to be fully compatible with the globally established Dräger Bodyguard 7000 electronic signal and warning unit, and the newly integrated PSS Merlin Modem.

For maximum protection the Dräger Bodyguard 7000 has an innovative compact design that integrates the power supply and pressure sensor modules within the back plate, creating a balanced weight distribution. Real-time monitoring of essential information such as time-to-whistle (based on current air consumption) and cylinder pressure is communicated via a lightweight handheld electronic gauge and display and/or, a facemask-mounted Head-Up Display (HUD).

Simultaneously this information can be transferred via the PSS Merlin Modem to an Entry Control Board or Xplore tablet / laptop PC running Dräger Merlin Software, further enhancing firefighter and fire ground safety.

Benefits

Dräger Bodyguard 7000 at a glance

- Accurate, continuously updated air time remaining
- Digital and Analogue display of cylinder pressure
- Time to whistle (based on current air consumption)
- Intuitive operation
- Integrated personal alert safety system (PASS)
- Visual and acoustic warnings and alarms (102 to 112 dBA)
- Easy push-button operation
- Configurable settings to suit individual preferences
- Enhanced display with scrolling text
- Automatic self tests and system tests
- Datalog with personal ID
- PC Link Software (Windows® compatible)
- Choice of operating modes: Tally and Automatic
- Simple upgrade to Dräger FPS® 7000 Head-Up- Display (HUD)
- Simple integration with the Dräger PSS Merlin Modem

Electronic monitoring with the Dräger Bodyguard 1500

The Dräger PSS 5000 can also be fitted with the Dräger Bodyguard 1500, a wireless PASS system which increases wearer safety in potentially hazardous situations. The system draws attention to colleagues in distress bygenerating distinctive visual and acoustic alert signals and features wireless data transmission from the Tx pressure gauge to the Bodyguard 1500 PASS device.

Dräger Bodyguard 1500 at a glance

- Twin blue fascia LED's enhance user safety by highlighting wearers position in areas of poor visibility
- Backlit Tx pressure gauge wirelessly transmits pressure data to Bodyguard 1500 PASS device and optional
 Heads up display
- Visual indication of low air pressure alerts on Tx gauge and Bodyguard 1500 PASS device.
- Integrated thermal alarm on Bodyguard 1500 PASS device alerts the wearer to exposure to elevated and rapidly rising temperatures
- Detachable Bodyguard 1500 PASS can be positioned anywhere on the wearer and can be detached for stand alone use.
- Both the Tx gauge and Bodyguard 1500 PASS devices incorporate datalogging capabilities for downloading incident history

System Components



Dräger FPS® 7000

The Dräger FPS® 7000 full face mask series sets new standards in terms of safety and wearing comfort. Thanks to its enhanced ergonomics and the availability of multiple sizes, it offers a large, optimised field of vision and a very comfortable, secure fit.



Dräger Compressed Air Breathing Cylinders

Designed using leading technology and advanced materials, Dräger's range of Composite Cylinders can be used in any application where breathing becomes difficult or impossible.



Dräger PSS® Lung Demand Valve (LDV)

Suitable for the most extreme applications whenever breathing apparatus has to be worn: with its compact and robust design, and excellent pneumatic performance, the Dräger PSS® Lung Demand Valve (LDV) will always deliver the air that you need.



Dräger Bodyguard® 1000

Designed to protect life by alerting the team when a wearer becomes motionless or distressed, the Dräger Bodyguard® 1000 emits clear and distinctive signals and alarms to ensure quick and effective recognition, even in the worst environmental conditions.

System Components



Dräger Bodyguard® 1500

Dräger Bodyguard® 1500 is an automatic wireless PASS system which increases wearer safety in potentially hazardous situations. The system draws attention to colleagues in distress by generating distinctive visual and acoustic alert signals and features wireless data transmission from the pressure gauge to the PASS device.



Dräger Bodyguard® 7000

The Dräger Bodyguard® 7000 is an electronic monitoring unit which provides continuous monitoring of personal information and operational status of the Dräger PSS® 7000 and PSS® 5000 self contained breathing apparatus.



Dräger PSS® Merlin® System

The Dräger PSS® Merlin® Telemetry System offers a precise overview of the status of respiratory equipment wearers. The vital status information is communicated directly between the entry control point and the wearer. Technology, which supports the incident, significantly increases safety and protects the lives of your breathing apparatus wearers.



Dräger FPS®-COM 5000

Because there is no time for misunderstandings in an emergency: The Dräger FPS®-COM 5000 communication unit has been specifically developed for the full-face mask Dräger FPS® 7000 and ensures clear communication through a voice amplifier unit or radio device — even under extreme conditions.

Accessories



Dräger PSS® Safety Belt

The Dräger PSS® Safety Belt increases wearer safety in potentially hazardous situations by securing the fire fighter whilst working at height: providing work positioning, fall prevention and emergency self-rescue. The multifunctional belt is designed to be easily integrated into the Dräger PSS® 5000 and PSS® 7000 SCBA to safely anchor the wearer, without the need for an additional belt.



Dräger FPS® 7000 Head-up Display (HUD)

One of the many benefits of the FPS® 7000 Facemask is the option of fitting a head up display. Always within the field of view the head up display allows easy monitoring of the cylinder contents without any manual action by the wearer.



Dräger PAS® ASV

The Dräger Automatic Switch over Valve (PAS® ASV) enables the user to connect compressed air breathing apparatus to an external air supply, such as a factory ring main, and be safe in the knowledge that if the external supply were to fail, there would be a safe and uninterrupted transition to the wearer's back-up air supply.



Dräger PSS® 7000 secondary supply hose

A range of secondary supply hoses for shoulder or waist mounting, to give flexibility of use in emergency rescue scenarios.

Related Products



Dräger PSS® 3000

The Dräger PSS® 3000 is a high performing breathing apparatus for firefighters. Combining comfort with exceptional pneumatic performance, it is designed for applications where simplicity and ease of use are key essentials. Lightweight yet robust, and easy to don, this advanced breathing apparatus provides the ultimate in breathing protection.



Dräger PSS® 4000

The Dräger PSS® 4000 is one of the lightest professional self-contained breathing apparatus for firefighters. Combining comfort with exceptional pneumatic performance, this SCBA is designed for applications where simplicity and ease of use are crucial. Lightweight yet robust, and easy to don, the PSS® 4000 provides outstanding breathing protection.



Dräger PSS® 7000

Developed by professionals for professionals, the Dräger PSS® 7000 breathing apparatus is a major milestone in our continuing development of breathing devices for the professional firefighter.

Technical Data

| | PSS® 5000 DS | PSS [®] 5000 DP | PSS [®] 5000 DP |
|-------------------------------|-----------------|--------------------------|--------------------------|
| | Pneumatic Gauge | Pneumatic Gauge | Bodyguard® 7000 |
| Weight Kg (Backplate and | 3.85 | 4.00 | 4.60 |
| Harness) | | | |
| Input Pressure (bar) | 0 – 300 | 0 – 300 | 0 – 300 |
| Nominal 1st Stage output | 7.5 | 7.5 | 7.5 |
| pressure | | | |
| 1st stage output flow (I/min) | > 1,000 | > 1,000 | > 1,000 |
| LDV output flow (I/min) | > 400 | > 400 | > 400 |
| Whistle activation pressure | 50 – 60 | 50 – 60 | 50 – 60 |
| (bar) | | | |
| Whistle Sound Level (dBA) | > 90 | > 90 | > 90 |
| ADSU Main alarm (dBA) | N/A | N/A | 102 – 112 |
| Approvals EN 137:2006 (Type | 2) | | |

Ordering Information

| Dräger PSS® 5000 Compr | essed Air Breathing Apparato | ıs | Description | Order No |
|-----------------------------------|------------------------------|-------------------|---------------------|-----------|
| Dräger PSS® 5000 DP | DIN Cyl. Thread | Single Cyl. Strap | Dräger PSS® 5000 DP | 33 57 845 |
| Pneumatic Gauge | connection | | SCS | |
| | | Univ. Cyl. Strap | Dräger PSS® 5000 DP | 33 58 333 |
| | 100 | | TCS | |
| | Cylinder Quick-Connect | Single Cyl. Strap | Dräger PSS® 5000 DP | 33 58 431 |
| | Barry Van | | QC SCS | |
| Dräger PSS® 5000 DP | DIN Cyl. Thread | Single Cyl. Strap | Dräger PSS® 5000 DP | 33 58 353 |
| Bodyguard® 7000 Button connection | | | BG 7000 SCS | |
| | | Univ. Cyl. Strap | Dräger PSS® 5000 DP | 33 58 355 |
| | | | BG 7000 TCS | |
| | Cylinder Quick-Connect | Single Cyl. Strap | Dräger PSS® 5000 DP | 33 58 436 |
| | | | BG 7000 QC SCS | |
| Dräger PSS® 5000 DP | DIN Cyl. Thread | Single Cyl. Strap | Dräger PSS® 5000 DP | 33 58 354 |
| Bodyguard® 7000 Tally | connection | | BG 7000 T SCS | |
| | | Univ. Cyl. Strap | Dräger PSS® 5000 DP | 33 58 356 |
| | | | BG 7000 T TCS | |
| | Cylinder Quick-Connect | Single Cyl. Strap | Dräger PSS® 5000 DP | 33 58 437 |
| | | | BG 7000 T QC SCS | |
| Dräger PSS® 5000 DS | DIN Cyl. Thread | Single Cyl. Strap | Dräger PSS® 5000 DS | 33 57 858 |
| Pneumatic Gauge | connection | | scs | |
| | | Univ. Cyl. Strap | Dräger PSS® 5000 DS | 33 58 338 |
| | | | TCS | |
| | Cylinder Quick-Connect | Single Cyl. Strap | Dräger PSS® 5000 DS | 33 58 428 |
| | _ | | QC SCS | |
| Dräger PSS® 5000 DS | DIN Cyl. Thread | Single Cyl. Strap | Dräger PSS® 5000 DS | 33 58 349 |
| Bodyguard® 7000 Button connection | | | BG 7000 SCS | |
| | | Univ. Cyl. Strap | Dräger PSS® 5000 DS | 33 58 341 |
| | | | BG 7000 TCS | |
| | Cylinder Quick-Connect | Single Cyl. Strap | Dräger PSS® 5000 DS | 33 58 434 |
| | _ | | BG 7000 QC SCS | |

Ordering Information

| Dräger PSS® 5000 DS Bodyguard® 7000 Tally | DIN Cyl. Thread connection | Single Cyl. Strap | Dräger PSS® 5000 DS BG 7000 T SCS | 33 58 350 |
|--|-------------------------------|---------------------------------|---|-----------|
| | | Univ. Cyl. Strap | Dräger PSS® 5000 DS BG 7000 T TCS | 33 58 352 |
| | Cylinder Quick-Connect | Single Cyl. Strap | Dräger PSS® 5000 DS BG 7000 T QC SCS | 33 58 435 |
| | vailable on the above variant | | | |
| | vailable on the above variant | S | | 22.57.042 |
| | atic Gauge (customizable) | 11. | | 33 57 943 |
| Drager PSS 5000 Bodygu | uard® 7000 Gauge (customi | zable) | | 33 58 824 |
| Dräger PSS® 5000 Modu | lar Upgrades / Accessories | | | Order No |
| Upgrade of PSS® 5000 wit | h pneumatic gauge to Bodygı | uard® 7000 (power supply | NOT included) | 33 57 101 |
| - button version | | | | |
| Upgrade of PSS® 5000 wit | h pneumatic gauge to Bodygı | uard® 7000 (power supply | NOT included) | 33 57 098 |
| - tally version | | | | |
| PSS® Merlin® Modem Kit | | | | 33 57 982 |
| Dräger FPS® 7000 HUD Ir | n-Mask display | <u> </u> | | 33 56555 |
| Dräger PSS® 7000 AA Batt | tery Pack (set of 5 batteries | included) | | 33 56556 |
| Dräger PSS® 7000 Rechar | rgeable Battery Pack (Ni Mh) | - for use with Dräger P | SS® Merlin® | 33 58121 |
| Dräger PSS® 7000 Rechar | geable Battery Pack (Ni Mh) - | for use without Dräger | PSS® Merlin® | 33 61 471 |
| | k Module (incl. PC Link Soft | | | 33 56 560 |
| | nal ID Cards (pack of 10) | | 100a | 33 56 561 |
| | female decontamination ho | ose w LF coupling | | 33 55 748 |
| Decontamination hose ma | | 1 0 | | 33 55 749 |
| T Piece (for 2 x 6.8L 300 b | par carbon composite cylind | ers) | | 33 37 660 |
| | pply hose (male and female | | | 33 56530 |
| | Kit w ASV (QR) Occasional | | | 33 55 844 |
| ASV Quick Fit | 33 57 007 | | | |
| Retaining Clip (for Gauge | e or Bodyguard 7000) | | | 33 52 089 |
| Waistbelt Loop | | | | 33 34968 |
| LDV Holder PI | | | | 33 57 527 |
| LDV Holder M45 | | | | 33 57 528 |
| LDV Holder ESA / RD40 | 33 57 526 | | | |
| Cheststrap | 33 39 280 | | | |
| Dräger PSS® Rescue Hoo | od | | | 33 54 982 |
| Dräger RPS 3500 (Rescu | 33 56 824 | | | |
| BA Set Hardshell Carrying | g Case (orange) | | | 33 35 412 |
| BA Set Hardshell Carrying | 40 59430 | | | |
| SCBA Holdall Carrying B | 33 56 473 | | | |
| Lung Demand Valves an | proved for use with Dräger | PSS® 5000 Compressed | Air Breathing Apparatus | Order No |
| Plus LDV Short Hose Push | 33 38 700 | | | |
| Plus LDV Short Hose Pus | 33 38 706 | | | |
| Plus LDV Short Hose Pus | 33 50 501 | | | |
| Plus LDV Short Hose ESA | 33 51 302 | | | |
| Plus LDV M40 1.75m (Re | 33 50 606 | | | |
| Plus LDV's with special p | oolymer diaphragm for use i | n H ₂ S environments | | Order No |
| Plus LDV Short Hose Push | 33 38 967 | | | |
| | | | | |
| Plus LDV Short Hose Pus | h M45 | | | 33 38968 |

Ordering Information

| 33 51 333 |
|------------|
| Order No |
| on request |
| on request |
| on request |
| |

