



# Dräger PARAT® 3100 Filtering Escape Device

The Dräger PARAT<sup>®</sup> 3100 is a half mask escape device equipped with a multi-gas ABEK15 filter. Packed in a robust and ergonomic case the unit is compact and easy to carry. Approved to the onlyrecognized standard forfiltering industrial escape devices (DIN 58647-7) – it provides users a minimum of 15 minutes escape time.



### Benefits

#### Proven protection against a variety of harmful gases

The multi-gas ABEK15 filter provides reliable protection against a wide range of toxic industrial gases.

#### Half mask with 2-point harness

Quick, easy and secure donning in an emergency situation. The half mask additionally allows for good communication.

#### Robust and ergonomic packaging

The ergonomic design with traction grip areas on the housing allows for easy and safe handling. It is easy to attach the device during daily work using the belt clip. The robust case provides stability and protection even under extreme working conditions.

#### **Transparent cover**

The cover is transparent and offers a clear view of the device. Service intervals are easy to keep track of as the expiration date is printed on the filter and can be easily read.

#### **Protection for at least 15 minutes**

The Dräger PARAT 3100 protects the user from a wide range of toxic industrial gases for at least 15 minutes. It is approved in accordance with DIN 58647-7.

#### Low cost of ownership

The device has a 12 year total service lifetime provided that the filter is replaced every 4 years, ensuring minimal operational costs.

### **Related Products**



#### Dräger PARAT® 3200

The Dräger PARAT<sup>®</sup> 3200 is a mouth piece / nose-clip escape device equipped with a multi-gas ABEK15 filter. Packed in a robust and ergonomic case the unit is compact and easy to carry. Approved to the only recognized standard for filtering industrial escape devices (DIN 58647-7) – it provides users a minimum of 15 minutes escape time.



## Technical Data

Filterperformance	ABEK15 gasfilterforprotection againstorganic and anorganicgases and vapours, approved in accordance to DIN 58647 part 7 at least 15 minutes 4 years maintenance free, filter exchange every 4 years, total shelf life 12 years Dräger PARAT <sup>®</sup> 3100 approx. 360 g		
Duration of use Shelf life Weight			
	Dräger PARAT® 3200	approx. 330 g	
Dimensions (Lx W x H)	Dräger PARAT <sup>®</sup> 3100	170 x 110 x 90 mm	
	Dräger PARAT <sup>®</sup> 3200	170 x 110 x 60 mm	
Approval	approved in accordance to DIN 58647 part 7 (CE mark 0158)		

#### Filter capacity according to DIN 58647-7\*

Туре	Test gas	Concentration in	Breakthrough in	Minimum breakthrough
		ppm	ppm	time in min
4	Cyclohexane (C <sub>6</sub> H <sub>12</sub> )	2,500	10	15
В	Chlorine (Cl <sub>2</sub> )	2,500	0.5	15
В	Hydrogen sulphide	2,500	10	15
	(H <sub>2</sub> S)			
В	Hydrogen cyanide	2,500	10	15
	(HCN)			
E	Sulphur dioxide (SO <sub>2</sub> )	2,500	5.0	15
к	Ammonia (NH <sub>3</sub> )	2,500	25	15
В	Hydrogen sulphide	10,000*	20	5
	(H <sub>2</sub> S)			
Test conditions: 30 L/mi	n, 70% relative humidity, 20°	c.		

\*\* To determine the breakthrough capacity of the gas filter it is additionally tested with 10,000 ppm hydrogen sulphide.

# Ordering Information

Dräger PARAT <sup>®</sup> 3100	R 57 981
HalfmaskwithABEK15filter	
Dräger PARAT® 3200	R 57982
Mouthbit with noseclip with ABEK15 filter	
Accessories for training units	
PARAT® 3100 Housing Cover, blue (training device component)	R 56 353
PARAT® 3200 Housing Cover, blue (training device component)	R 56 354
Replacement filters and parts	
ABEK15 Replacement Filter (5 pieces)	R 57983
PARAT <sup>®</sup> 3000 Security Tag (50 pieces)	R 56 355
PARAT <sup>®</sup> 3000 TPE Sealing Strap	R 56 319
PARAT® 3000 Carrying Belt	R 28 175



(T) +971 255 17786 (T) +971 451 47114 (F) +971 266 63089

0

ISO 9001:2015 ISO 29001:2010

P.O.Box 27301, ICAD III, Musaffah Sout Abu Dhabi, United Arab Emirates www.eastwindsafety.com