

Dräger Flame 1500 (IR3) Flame Detector

The Dräger Flame 1500 flame detector uses its triple IR sensor to detect hydrocarbon fires even at great distances. It offers you high reliability against false alarms.



Benefits

Fast and reliable flame detection

The Dräger Flame 1500 is equipped with three infrared sensors. They enable it to detect hydrocarbon-based fires even at a great distance. This reliability allows it to meet IEC 61508 requirements for safety integrity according to SIL2. The flame detector also has a HART® interfaces via which it can be connected directly to the fire alarm system, for example. In addition, the Flame 1500 has a low power consumption.

Prevention of false alarms

The Flame 1500 measures infrared radiation in three different wavelengths and compares them with the reference value of CO₂, which is produced during the combustion of hydrocarbons. In combination with the analysis of the flame's flickering, the complex algorithm identifies a fire and excludes sources of interference. In this way, the Flame 1500 reliably prevents false alarms caused by possible fault sources such as welding work or black body radiation.

Robust and resistant

The powder-coated housing made of stainless steel or aluminum is very robust and weatherproof. The viewing window is heated to protect against icing and fogging. This allows you to operate the Flame 1500 reliably under a wide range of environmental conditions.

Simple check

The Optical Verification Test (OVT) automatically checks the electronics and optics of the Flame 1500 without affecting the field of view. The three-colour LED on the front lets you quickly see the status of the unit. Green stands for normal operation, yellow indicates a fault and red signals a fire alarm.

Accessories



Dräger FS-5000

The Dräger FS-5000 flame simulator is used to simulate the presence of fire or flames to test the correct operation of the Dräger Flame 5000, 3000 or 1500.

Related Products



Dräger Flame 5000

The Dräger Flame 5000 is an imaging based explosion proof flame detector. This visual flame detection system uses digital image processing and advanced algorithms to process and interpret flame characteristics. This principle offers an extended field of view and fewer false alarms. Each detector is equipped with a colour CCTV camera.



Dräger Flame 3000

The Dräger Flame 3000 is an imaging based explosion proof flame detector. This visual flame detection system uses digital image processing and advanced algorithms to process and interpret flame characteristics. This principle offers an extended field of view and fewer false alarms.

Technical Data

Dräger Flame 1500

Type	Explosion-proof multi-spectrum (triple) IR flame detector	
Spectral range	Three wavelengths in the range from 3 µm to 8 µm	
Field of view	Horizontal 90°, vertical 90°	
Response time	4 seconds (typical)	
Sensitivity settings	Low 15 m, Medium 30 m (standard) and High 60 m	
Measuring range*	n-Heptane/gasoline	60 m (200 ft)
	Methanol	42 m (136 ft)
	Methane	50 m (165 ft)

*Fire pan 0.1 m²(1ft²), flaring fire 0.6 m (3 ft)

Electrical data

Relay	Alarm and fault
Signal output	0 to 20 mA
Communication	RS485, HART® 7
Supply voltage	24 VDC nominal (18 to 32 VDC)
Power consumption	Minimum 3 W / maximum 12 W with heating

Housing

Material	Aluminium or stainless steel, powder-coated
Cable gland	Dual M25 or ¾"NPT
Weight	2.5 kg (5.5 lbs.) aluminium or 6 kg (13.2 lbs.) stainless steel
Protection class	IP66, NEMA 4X

Environmental conditions

Temperature	-60 to +85 °C (-76 to +185 °F)
-------------	--------------------------------

Approvals

ATEX	Ex II 2 G Ex db IIC T4 Gb IP66
IECEx	Ex II 2 G Ex db IIC T4 Gb IP66
FM/FMC	Class 1 Zone 1 AEx db IIC T4
	Class 1 Div. 1, Groups B, C, D T4
EAC TR CU	Requested
CCCF	Requested
INMETRO, PESO, etc.	On request
Functional Safety	SIL2 certified

Ordering Information

Dräger Flame 1500	Order number
Dräger Flame 1500, Aluminum, 2 x M25	37 21 519
Dräger Flame 1500, Aluminum, 2 x ¾" NPT	37 21 517
Dräger Flame 1500, Stainless Steel, 2 x M25	37 21 518
Dräger Flame 1500, Stainless Steel, 2 x ¾" NPT	37 21 516
Accessories	Order number
Dräger FS-5000	42 09 307
Bracket Standard – 316 stainless steel	37 18 732
Bracket Marine – 316 stainless steel	37 01 298
Sealing Kit Detector – metric	37 01 303
Sunshield – Flame 1x00/3x00/5x00	37 01 299
Mount Kit – 2" pole	37 01 300
Mount Kit – 3" pole	37 01 301
Mount Kit – 4" pole	37 01 302



Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.
61 Science Park Road
The Galen #04-01
Singapore 117525
Tel: +65 6872 9288
Fax: +65 6259 0398
asia.pacific@draeger.com

**REGION CENTRAL
AND SOUTH AMERICA**

Dräger Indústria e Comércio Ltda.
Al. Pucurui - 51 - Tamboré
06406-100 - Barueri - SP
Tel. +55 (11) 4689-4900
relacionamento@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact



(T) +971 255 17786
(T) +971 451 47114
(F) +971 266 63089

ISO 9001:2015
ISO 29001:2010



P.O.Box 27301, ICAD III, Musaffah South
Abudhabi, United Arab Emirates
www.eastwindsafety.com