

Dräger X-zone® 5800 Area Monitor

State-of-the-art area monitoring – the Dräger X-zone® 5800 in combination with the Dräger X-am® 5000, 5100 or 5600 gas detection instruments can be used for the measurement of up to six gases. The internal pump and continuous power supply in the explosive area of zone 0 extend the range of applications in mobile gas detection technology.



Dräger X-zone® 5800



D-21262-2020

Benefits

Area monitor

- combination with Dräger X-am® 5000, 5100 or 5600 – measurement of up to 6 gases
 - extensive area monitoring thanks to fenceline of up to 25 devices
 - option for permanent power supply in explosive areas (zone 0)
-

Innovative area monitoring

The Dräger X-zone 5800 transforms the Dräger personal gas detection instruments X-am 5000, 5100 and 5600 into innovative area monitoring devices for a wide range of applications. A patented combination for increased safety – in addition to the personal air monitors carried on the body, these area monitors are positioned where gas hazards are expected.

Clear warning

Even from a distance, the illuminated green LED ring indicates that the air is free of toxic and combustible gases. Upon detection of gas hazards, the LED color changes from green to red, thus providing a clear visual warning that gas is present. Additionally, a loud and highly audible evacuation alarm is emitted. The Dräger X-zone 5800 gas entry location permits gas to diffuse into the Dräger X-am 5000, 5100 or 5600 from all sides.

Wireless fenceline

Up to 25 Dräger X-zone 5800 can be automatically interconnected to form a wireless fenceline. The interconnection of the area monitoring devices allows for rapid establishment of safety networks for larger areas.

A Dräger X-zone 5800 detecting a gas alarm transmits the alarm signal to all interconnected units. A red flashing master alarm in the unit detecting the gas contrasts with red/green flashing alarms of the connected units. This provides simple recognition of alarm status and the actual location of the hazard.

With the corresponding configuration, the maximum gas concentration in the monitored area is shown on the display. Combined with the display of the X-zone ID a clear containment of the hazard area is possible.

Continuous operation for up to 120 hours

The 24 Ah battery of the Dräger X-zone 5800 provides up to 120 hours of continuous operation – up to a complete working week.

The Power Supply Ex is available for continuous use of the X-zone 5800. It offers a 50 m supply from a safe area to a potentially explosive area and is even approved for use with the X-zone 5800 in Zone 0.

For safe transport, the cable of the Power Supply Ex is rolled up on a cable drum in which the power supply is also integrated.

Benefits

Pump or diffusion mode – suitable for your respective application

The X-zone 5800 offers you both the possibility to draw in gas from a distance of up to 30 m in pump mode and the use in diffusion mode. The switch between these two options takes less than a minute. Simply exchange the pump cover or the supplied diffusion cover against each other. The X-zone 5800 is ready for another measuring operation – without any tools.

Other benefits

- 360°-gas entry
- Approval for Ex-Zone 0
- individually configurable with the Dräger CC-Vision PC software (e.g. alarm frequency)
- inductive charging station: easy and convenient non-contact charging (outside the Ex-area)

Interfaces

The interfaces on the back of the device offer the possibility of switching actuators in case of alarms by means of the configurable relay. The interface can also directly forward device data, such as measured values of sensors and alarms, via Modbus protocol. This allows you to integrate the devices into existing evaluation units.

System Components



D-21278-2020

Power Supply Ex

The Power Supply Ex enables the X-zone 5800 to be continuously supplied with power even within an explosion-proof area.

System Components

D-14325-2017



Dräger X-am® 5000

The Dräger X-am® 5000 belongs to a generation of gas detectors, developed especially for personal monitoring applications. This 1- to 5-gas detector reliably measures combustible gases and vapors as well as oxygen and harmful concentrations of toxic gases, organic vapors, Odorant and Amine.

D-31721-2011



Dräger X-am® 5100

For manufacturing petrochemical products, aseptic packing, or handling of rocket fuel: the Dräger X-am® 5100 portable single-gas detector ensures that you use the safest methods possible for handling HF, HCl, H₂O₂ or hydrazine – thanks to proven Dräger sensor technology and a device design which is perfectly customised to reactive gases.

D-23837-2009



Dräger X-am® 5600

Featuring an ergonomic design and innovative infrared sensor technology, the Dräger X-am® 5600 is one of the smallest gas detection instrument for the measurement of up to 6 gases. Ideal for personal monitoring applications, this robust and water-tight detector provides accurate, reliable measurements of flammable and toxic gases and vapors as well as oxygen.

Accessories



D-23825-2009

Bump test adapter

For function tests



D-27768-2009

Alarm damper

For use within bump tests



D-23831-2009

Socket

For measurements of light gases



D-23634-2009

Induction charger

Allowing easy charging

Accessories

D-1568-2010



Plug-in charger

100 – 240 V

D-10391-2009



Float probe

With 5 m or 16.4 ft. FKM hose

D-1571-2010



Hose set

Consisting of water trap, dust and water filter

D-30746-2015



Dräger Configuration and Evaluation Software

Save measurement results, professionally configure gas detection instruments and viewing performance data – all that is possible with the tailor-made Dräger software.

Accessories



D-0494-2018

Calibration gas and accessories

Calibration of equipment will ensure safe operation and functionality of equipment and will also meet with the applicable regulations and codes of practice. Various calibration options are easily available.

Related Products



D-2754-2018

Dräger X-am® 2500

The Dräger X-am® 2500 was especially developed for use as personal protection. The 1 to 4 gas detector reliably detects combustible gases and vapours, as well as O₂, CO, H₂S, NO₂ and SO₂. Reliable and fully mature measuring technology, durable sensors and easy handling ensure a high degree of safety with extremely low operating costs.



D-6491-2017

Dräger X-am® 8000

Clearance measurement was never this easy and convenient: The 1 to 7 gas detector detects toxic and flammable gases as well as vapours and oxygen all at once – either in pump or diffusion mode. Innovative signalling design and handy assistant functions ensure complete safety throughout the process.

Technical Data

Dräger X-zone® 5800

Dimensions (W x H x D)	490 x 300 x 300 mm 20 x 12 x 12 in.	
Weight	10 kg (22 lbs.) (24 Ah battery)	
Ambient conditions	Temperature: -20 °C - max. +50 °C / -4 °F - max. +122 °F Pressure: 700 to 1,300 hPa Humidity: 10 to 95 % r.h.	
Ingress Protection	IP67	
Alarm	Visual 360° LED (illuminated ring) Audible 360°; >108 dB in a distance of 1 m (3 ft.), 120 dB in a distance of 30 cm (1 ft.) Configurable alarm patterns, frequencies and volumes	
Life signal	Green status display (360°), illuminated ring (LED)	
Operating time	Approx. 120 h (24 Ah battery) Depending on sensor equipment / configuration of the life signal	
Charging time	Approx. 14 h Flexible power supply: External 100 – 240 V charger (worldwide) or inductive wireless charger	
Pump operation	Maximum hose length: 45 m (150 ft.), 30 m (100 ft.) for zone 0	
Alarm output	Potential-free alarm contact for intrinsically safe circuits (6-pole); <20 V to 0.25 A (0.15 A constant current); Resisting load	
Radio transmission	Worldwide license-free ISM frequencies Digital radio, robust and interference-free transmission up to 100 m (328 ft.)	
RF approvals	868 MHz (EU, Norway, Switzerland), 915 MHz (USA, Canada, Singapore, Australia), 433 MHz (Russia, Malaysia)	
Approvals	ATEX	I M1 Ex ia I Ma II 1G Ex ia IIC T4 Ga
	IECEX	Ex ia I Ma Ex ia IIC T4 Ga
Power Supply Ex		
Dimensions	365 x 320 x 250 mm	
Weight	10 kg	
Protection class	IP 44	
Approvals	ATEX	II (1)G [Ex ia Ga] IIC
	IEC Ex	[Ex ia Ga] IIC
	CSA/US	pending
Temperature range	-20 °C to +50 °C	
Cable length	Cable drum 50 m	
	Connection cable fix 0.5 m + Power Cord EU, UK, US or AUS 3 m	

Ordering Information

Dräger X-zone® 5800	Part-No.
Dräger X-zone® 5800 433 MHz, 24 Ah pump	83 29 020
Dräger X-zone® 5800 868 MHz, 24 Ah pump	83 29 030
Dräger X-zone® 5800 915 MHz, 24 Ah pump	83 29 040
Gas supply adapter	83 23 314
Alarm damper	83 20 110
Socket, 25 cm high (12 in.)	83 20 645
Set: cap for Dräger X-am® 5100 for X-zone® with pump	83 23 938
Power Supply ex-approved area	
Power Supply Ex 230 V w/o power cord	83 29 000
Power Supply Ex 110 V w/o power cord	83 29 010
Power cord EU	83 29 180
Power cord UK	83 25 392
Power cord AUS	83 25 393
Power cord USA	83 29 049
Charging accessories	
Inductive charger with power supply:	
For USA, Japan	83 22 076
For UK	83 22 077
For China, Australia	83 22 078
For South Africa	83 22 079
For Europe, Russia	83 22 080
Plug-in charger	83 20 749
Pump accessories	
Float probe with 5 m or 16.4 ft. FKM hose	83 18 371
Hose set (consisting of water trap, dust and water filter)	83 21 527
Hose, electronically conductive	11 80 681
FKM hose, solvent-resistant	12 03 150
Tygon® hose	83 20 766
Communication accessories	
Dräger CC-Vision	www.draeger.com/software
USB DIRA with USB cable	83 17 409
X-zone® Com	
Cloud license 1 year	83 25 346
Revaluate SIM Card (150 € / service charge)	83 26 896
Power Supply X-zone Com	83 24 374
Set straps for X-zone Com	83 24 377
Set rubber feet with clamps for X-zone	83 24 384
Magnetic pen	45 44 101

Tygon® is a registered trademark of Saint-Gobain Corporation.

Notes





Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.
61 Science Park Road
The Galen #04-01
Singapore 117525
Tel: +65 6872 9288
Fax: +65 6259 0398
asia.pacific@draeger.com

**REGION CENTRAL
AND SOUTH AMERICA**

Draeger Panamá Comercial
S. de R.L.
59 East Street, Nuevo Paitilla,
House 31, San Francisco Town
Panama City, Panama
Tel +507 377-9100 / Fax -9130
servicioalcliente@draeger.com

REGION NORTH AMERICA

Draeger, Inc.
3135 Quarry Road
Telford, PA 18969
Tel +1 800 4DRAGER
(+1 800 437 2437)
Fax +1 215 723 5935
info.usa@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact



(T) +971 255 17786
(T) +971 451 47114
(F) +971 266 63089

ISO 9001:2015
ISO 29001:2010



P.O.Box 27301, ICAD III, Musaffah South
Abudhabi, United Arab Emirates
www.eastwindsafety.com