



Dräger Saver CF Emergency Escape Breathing Apparatus (EEBA)

The Dräger Saver CF constant flow Emergency Escape Breathing Apparatus allows safe, effective and uncomplicated escape from hazardous environments. Simple toputon and featuring practically automatic operation, this hood-based, positive-pressure breathing device can be used with minimal training.



WHEN TIME IS OF THE ESSENCE

In emergency situations, conditions can deteriorate rapidly. The air is suddenly filled with smoke or toxic fumes and rapid escape is the only available option. The Dräger Saver CF is highly visible and was designed to be suitable even for people with spectacles or facial hair. When opened, the Dräger Saver CF is automatically activated and begins feeding a continuous supply of breathing air. The Saver CF gives the wearer the precious additional time needed to exit the area safely.

HIGHLY VISIBLE, EVEN UNDER ADVERSE CONDITIONS

Available with either a soft bag or hard case, the Saver CF can be easily wallmounted in strategic locations in potentially hazardous areas. Both black anti-static cases or bright orange bags feature photoluminescent panels and reflective stripes for enhanced visibility, even under low lighting conditions. The Saver CF is compact and lightweight and can be warn either as a chest bag or over the shoulder. Made from highly resistant materials, it is washable, flame retardant and allows water to drainfreely.

UP TO 15 MINUTES OF LIFESAVING AIR

The Dräger Saver CF utilizes a simple, fail-safe reducer system with excellent flow characteristics, providing a consistent rate of air flow until the cylinder is completely empty. An alarm whistle soundsbeforetheair supplyisexhausted. It can be equipped with cylinders which can hold either a 10 or 15 minute supply of air. The flame-retardant hood incorporates a large visor for maximum peripheral vision.

NEW OPTIONS FOR ADDED SAFETY AND DURABILITY

The SE version includes a newly developed elastic neck seal which offers unparalleled resistance to the effects of high temperatures, ozone and diesel fumes, which are often found in places such as engine rooms. This translates to years of reliable, worry-free service, evenunder adverseconditions. Standard Dräger Saver CF15 units can also be retrofitted with the SE option.



Dräger Saver CF – hard case



Dräger Saver CF soft bag



DRÄGER SAVER CF – FOR YOUR SAFE ESCAPE



The Dräger Saver CF requires very little service or maintenance. A transparent window on both the soft bag and hard case lets you check the cylinder pressure gauge easily without unpacking the unit. Youknow the Dräger Saver CF istherefor you when you need it.

NORMS

The Dräger Saver CF complies with EN1146 (2005), Lloyd's Register Certificate of Fire Approval and Lloyd's Register Certificate of Type Approval. It also complies with SOLAS Chapter II-2, the Marine Equipment Directive, the Pressure

Equipment Directive and ISO 23269-1:2008. Anti-static versions are also suitable for use in explosive atmospheres (ATEX zone 0).



Dräger Saver CF hard case



Dräger Saver CF soft bag

TECHNICAL DATA

	Dräger Saver CF		
Size (H x L x D)	510 x 260 x 190 mm		
Cylinder charging pressure	200 bar		
Airflow tothe hood	35-37 L/min		
Operating temperature range	-15 °C to +60 °C		
Approvals	EN1146 (2005), ISO 23269-1:2008, SOLAS Chapter II-2, the Marine Equipment Directive and the Pressure Equip-		
	ment Directive. The Dräger Saver CF anti-static issuitable for use in explosive atmospheres (ATEX zone 0).		
	CF10	CF15	
Weight (Kg) including cylinder			
Hardcase	5.9 kg	6.9 kg	
Soft bag	4.2 kg	5.2 kg	
Cylinder	2L 200 bar	3L 200 bar	

ORDER INFORMATION

Saver CF10	3359734
Saver CF <mark>15</mark>	3359735
Saver CF10 Anti-static	3359736
Saver CF15 Anti-static	3359737
Saver CF <mark>15 (SE)</mark>	3359742
Saver CF15 (SE) Anti-static	3359743

Dräger Saver CF - Hard case versions

Saver CF10	3359739
Saver CF15	3357940
Saver CF15 (SE)	3359744

Accessories

3360340
3360339
3360341
3350396
3350388
3350431
3350424
3351823

Safety Wash

– 1 liter dispenser	3380164
– 1 liter refill	3380165
– 5 liter dispenser	3380166
– 5 liter refill	3380167



(T) +971 255 17786
(T) +971 451 47114
(F) +971 266 63089

ISO 9001:2015 ISO 29001:2010 P.O.Box 27301, ICAD III, Musaffah South
Abu Dhabi, United Arab Emirates
www.eastwindsafety.com