

# Dräger LAR 7000 Diving Equipment

Dräger LAR 7000 is a very versatile diving apparatus for all facets of shallow water diving, including VSW – MCM diving and submarine lock-out as well as special operations diving.



### **Benefits**

### **Features**

- Closed circuit oxygen diving combined with semi closed circuit nitrox diving
- Switching between oxygen and nitrox diving mode can be made during a dive
- Front mounted apparatus
- Horizontal or vertical oriented nitrox cylinder back mounted
- Quick release nitrox connection (one hand operation)
- None magnetic in compliance with STANAG 2897 class A

### Related Products



### Dräger LAR 5000

LAR 5000 is a very streamlined and compact diving apparatus for special operations diving. Optionally the apparatus can be supplied from a nitrox regulator for submarine lock-out. With its fold-in pressure gauge, LAR 5000 embodies a streamlined rebreather for military use.



### Dräger LAR VII Combi FA

Dräger LAR VII Combi FA is a very versatile and compact diving apparatus for all facets of shallow water diving, including VSW – MCM diving and submarine lock-out as well as special operations diving.

0000

## **Related Products**



### Dräger DiveSorb® Pro

The Dräger DiveSorb $^{\circ}$  Pro was developed specifically for closed or semi-closed rebreathers in order to allow a high degree of CO $_2$  absorption, and thus long dive times.

# Technical Data

### Basic Unit

Principal of operation	closed and semi-closed circuit, with constant dosage and lung demand valve		
Diving depth	0 to 10 msw in closed circuit		
	0 to 24 msw in semi-closed circuit		
Diving endurance	240 minutes at 4° C water temperature		
Breathing gas	0 to 10 msw pure oxygen		
	0 to 24 msw pre-mixed gas B, 60 % $O_2$ , 40 % $N2$		
	optional with upgrade kit:		
	0 to 42 msw pre-mixed gas C, 40 % O <sub>2</sub> , 60 % N2		
	0 to 54 msw pre-mixed gas D, 32,5 % $\mathrm{O}_2$ , 67,5 % $\mathrm{N}2$		
Breathing bag	flexible volume approx. 5.5 I		
	available volume approx. 10 l		
Sodalime	DiveSorb® Pro; approx. 2.3 kg per filling		
Relief valve	adjustable from approx. 4 mbar to 90 mbar		
Magnetic signature	conforming to STANAG 2897, Class A		
Acoustic signature	tested in accordance with AMP 15		
Dimensions	lenght 435 mm, width 340 mm, depth 190 mm		
Weight	in air	approx. 13 kg	
	in water (ready to dive)	neutral	
Operating temperature	minus 2° C to 40° C		
Storage temperature	minus 30° C to 50° C		

### CYLINDER DATA

Cylinder oxygen	non-magnetic	low magnetic (LM)	magnetic
Volume	2.0	1.9	1.5 l
Diameter	140 mm	134 mm	115 mm
Nominal Pressure	200 bar	200 bar	200 bar
Connection	G 3/4"	G 3/4"	G 3/4"
Material	carbon composite	aluminium alloy	steel
Approval	type approval / TÜV	DOT3AL	type approval / TÜV
Positioning	at the apparatus	at the apparatus	at the apparatus
Cylinder mixgas	non-magnetic	low magnetic	magnetic
Volume	4.0	2.7	4.0
Diameter	140 mm	117 mm	135 mm
Nominal Pressure	200 bar	200 bar	200 bar
Connection	G 3/4"	G 3/4"	G 3/4"
Material	carbon composite	aluminium alloy	steel
Approval	Type approval (TÜV)	TÜV	TÜV
Positioning	at the back	at the back	at the back
Valve Hand Wheel Right + Left	yes	yes	no

# Ordering Information

Dräger LAR 7000 without harness	T 16 410
Cylinders	
Oxygen cylinder - NM, 2 I, with valve, black colour, STANAG 'A'	T 16 991
Oxygen cylinder – LM, 1.9 I, with valve, black colour	T 13 401

# Ordering Information

Oxygen cylinder (filled) - magnetic, 1.5 l, with valve, black colour,	B 03 961
steel	
Mixgas cylinder - NM, 4 I, with valve, black colour, STANAG 'A',	T 16 992
for left side	
Mixgas cylinder - NM, 4 I, with valve, black colour, STANAG 'A',	T 16 993
for right side	
Mixgas cylinder – LM, 2.7 l, with valve, black colour, for right side	T 16 805
Mixgas cylinder – LM, 2.7 l, with valve, black colour, for left side	T 16 808
Mixgas cylinder - magnetic, 4 l, with valve, black colour	T 15 109
Test Accessories	
Pre Dive Test Unit (Pre Dive)	T 14 992
Dosage Test Unit (Workshop)	T 14 433
Multi-Purpose Test Unit (Workshop & Pre Dive)	T 15 007
Accessories	
Transport case, plastic composite, large with inlets	T 16 956
Tactical Harness 1000 – Basic version, size S	T 92 169
Tactical Harness 1000 - Basic version, size M	T 92 161
Tactical Harness 1000 – Basic version, size L	T 92 165
Tactical Harness 1000 – Basic version, size XL	T 92 166
Standard Harness consisting of neck and waist belt	T 15 425
Diving goggle, black, magnetic with twin visor mask	T 53 307
Diving goggle, black, NM with twin visor mask	T 16 471
Bail out regulator, with mouth piece hose and switch of valve	T 15 760
Bail out regulator, with push in connector for face mask, hose and	T 16 420
switch of valve	
Tools	
Tool bag	T 14 410
Tool bag, NM	T 16 405
Spare Parts	
Spare Parts Set	T 14 411
Consumable	
DiveSorb® Pro, 4.5 kg / approx. two dives	67 37 062
DiveSorb® Pro, 18 kg / approx. eight dives	67 37 109
Halocarbon lubricant ( 28 g per tube )	65 90 212
Silicon lubricant (100 g per tube) for mouthpiece	15 95 008
Molykote M 111 Comp. 100G	15 63 572
Christolube MCG 111	40 54 602

# 90 46 491 | 17.03-4 | Subject to modifications | © 2017 Drägerwerk AG & Co. KGaA

Notes

Not all products, features, or services are for sale in all countries. Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

### CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA Moislinger Allee 53–55 23558 Lübeck, Germany www.draeger.com

### **REGION DACH**

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

### REGION EUROPE

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

### REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA Branch Office P.O. Box 505108 Dubai, United Arab Emirates Tel +971 4 4294 600 Fax +971 4 4294 699 contactuae@draeger.com

### REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd. 25 International Business Park #04-20/21 German Centre Singapore 609916 Tel +65 6308 9400 Fax +65 6308 9401 asia.pacific@draeger.com

# REGION CENTRAL AND SOUTH AMERICA

Dräger Panama S. de R.L. Complejo Business Park, V tower, 10th floor Panama City Tel +507 377-9100 Fax +507 377-9130 contactcsa@draeger.com

Locate your Regional Sales Representative at: www.draeger.com/contact

